

# METHOD AND APPARATUS FOR REDUCING ENGINE CYCLING IN HYBRID ELECTRIC VEHICLE

## Technical Field

5 This invention relates in general to hybrid motor vehicles operable by either an electric motor or a liquid fuel powered internal combustion engine and, in particular, to a method and system for reducing the cycling of the engine during non-propulsive operations.

## Background Art

10 For various reasons, including environmental reasons, it is desirable to provide automotive vehicles that operate with propulsion systems other than the typical internal combustion engine. One such propulsion system contemplated is a purely electric vehicle.  
15 However, because of well known problems associated with such electrical vehicles, combining the electric drive with a somewhat more conventional internal combustion engine is one alternative being considered. A vehicle with such an alternative propulsion system is generally  
20 referred to as a hybrid motor vehicle.

A hybrid electric vehicle (HEV) is generally described as a motor vehicle with a main power unit (HPU) which converts fuel energy to electric and/or mechanical energy, and a bidirectional energy storage  
25 system (ESS), usually electrical. The main power unit may be a piston engine, gas turbine, fuel cell or the like, while the energy storage system may be a battery, flywheel, capacitor or the like.

005760-5759960

Motive power to drive the vehicle, as demanded by the driver, is drawn from a combination of these two sources. The essential elements of a hybrid vehicle powertrain include an HPU, an electric traction  
5 motor-generator, and an ESS. Various hybrid configurations add HPU and ESS power in different places in the system.

The emissions that occur at engine startup are at a high level due to the fact that the air/fuel ratio  
10 is not accurately determined on startup and the catalytic converter is usually cold (unless it is electrically heated). Upon startup, initial emissions are high due to low catalyst efficiency until the catalyst temperature is stabilized. It is, therefore,  
15 desirable to limit the frequency of engine starts in a given drive cycle. Emissions are much lower if the engine is requested to remain on for a short extended period beyond driver demand (accelerator) to satisfy ancillary requirements. During this extended run  
20 period, the catalyst is sufficiently hot from the ongoing combustion process to perform the catalytic action required to maintain low emissions.

Ancillary functions that require engine operation include, but are not limited to: brake  
25 booster vacuum, fuel vapor purge, and passenger compartment heating or air conditioning. It is an object of the present invention to reduce the number of times that the engine or other main power unit is turned on solely for supporting non-propulsive or ancillary  
30 functions to thereby enhance both fuel economy and reduce engine emissions.

## Disclosure Of Invention

005750 5750960

In accordance with the present invention, a method and system is provided that responds to non-propulsive needs of a hybrid vehicle by setting at least two thresholds related to engine support: a first threshold to keep a running engine ON, and a second threshold to turn the engine ON from an OFF state. More particularly, a request is made that the engine not be turned OFF until the value of an auxiliary system parameter exceeds the first threshold value and that the engine be turned ON if the parameter falls below the second threshold value. In other words, if the engine is OFF when the value of the parameter falls below the second threshold value, a request is made that the engine be turned ON and whenever the engine is ON, a request is made that the engine be maintained ON until the parameter exceeds the first threshold value.

The logic expressed above will extend engine run time slightly but will reduce the frequency of engine startups. This can be calibrated for a clear emissions improvement and a modest fuel economy improvement.

## Brief Description Of Drawings

Figure 1 is a schematic block diagram of the system of the present invention; and

Figure 2 is a flowchart of the method of implementing the invention.

### Best Mode For Carrying Out The Invention

Referring now to the drawings and initially to Figure 1, a series hybrid electric vehicle (HEV) 10 is illustrated. The HEV 10 contains a main power unit (HPU) 12, for example an internal combustion engine, which uses fuel from an onboard fuel tank 14 to generate electricity in a motor-generator (MG) 16 to power the vehicle 10. An energy storage system (ESS), such as a battery 18, is also used to power the vehicle alone or in combination with the HPU 12. A direct mechanical linkage, shown in dashed lines, may be included to provide a parallel configuration.

Both the HPU 12 and ESS 18 are under the control of a controller 20. Though not shown in detail the controller hardware is conventional and includes the usual components, such as a processor ("CPU"); input/output ports; an electronic storage medium or read-only memory containing processor-executable instructions and calibration values ("ROM"); random-access memory ("RAM"); "keep-alive" memory ("KAM"); and a data bus of any suitable configuration. While the controller will be discussed as a single computer, it will be understood by those skilled in the art that a plurality of processors or separate interconnected computers may be employed. As illustrated, the vehicle 10 contains a motor/transaxle 22 for delivering power from the HPU and ESS to the vehicle wheels 24. The proportion of the total motive demand power (MDP) power derived from the HPU and ESS depends upon the operational strategy method employed.

The controller 20 receives signals from a variety of sensors coupled to the unit 12 and/or the

005150 3459360

vehicle and controls the operation of the unit 12 and various ancillary subsystems. The sensors indicated in Figure 1 include an air charge temperature sensor 26 providing input to the controller 20 for controlling a  
5 purge subsystem 28, a vacuum sensor 30 providing input for controlling a brake and/or other vacuum operated subsystem generally indicated at 32, one or more temperature sensors 34 providing input for controlling a heating, ventilating and air conditioning (HVAC)  
10 subsystem generally indicated at 36, and a catalyst temperature sensor 38 providing input for monitoring catalyst efficiency. The aforementioned subsystems are illustrative only and not intended to limit the type of subsystems to which the invention may be applied.

15 Referring now to Figure 2, a flowchart depicting the method of the present invention is shown. A check is made at decision block 40 to determine if the engine is running, and if so, "ENGINE ON" thresholds are set at block 42. If all auxiliary systems are above  
20 their respective "ENGINE ON" thresholds as determined in block 44, then an engine ON flag is cleared at 46 which permits the engine to be turned OFF as dictated by other considerations. If the thresholds of any of the auxiliary systems are below their respective "ENGINE ON"  
25 thresholds, the engine ON flag is set at block 48. On the other hand, if the engine is OFF as determined at block 40, then the "ENGINE OFF" thresholds of the various subsystems are set at block 50. If any of the auxiliary systems are below their respective "ENGINE  
30 OFF" thresholds as determined in block 52, then the engine ON flag is set at block 48 which requests the engine be turned ON. If the thresholds of all of the auxiliary systems are above their respective "ENGINE



00563515 091500

70°, the a/c compressor would remain ON until a temperature of 68° is reached, and a request is made that the engine remain ON until that temperature is reached. When the engine is OFF, a temperature of 72°  
5 would be reached before a request is made that the engine be turned ON to support running the a/c compressor.

This logic is also used to provide a reduction in control of purge of fuel vapor while the engine is  
10 not running (this level is also calibratable). Rather than a single threshold, engine turn-on is based on a plurality of conditions, including, but not limited to: ambient temperature, time since last engine run, duration of last engine run, and last recorded purge  
15 vapor level while running. The objective is to characterize the fuel vapor being stored in the carbon canister as best as possible and to purge the vapor as completely as possible.

It is well known that a cool catalyst is  
20 inefficient. Thus, when the engine is first turned ON and the catalyst is cold, emissions are relatively high until the exhaust heats the catalyst to a sufficient temperature to perform catalytic action. It is desirable to monitor the output of the catalyst  
25 temperature model and maintain the engine ON for one temperature threshold and turn the engine ON at a lower threshold in order to improve emissions. This approach provides a cost savings over electrically heating the catalyst to maintain the proper catalyst temperature.

30 While the best mode for carrying out the invention has been described in detail, those familiar with the art to which this invention relates will recognize various alternative designs and embodiments

for practicing the invention as defined by the following claims.

096343 091500